

Main

Range of product	EOCR
Device short name	PMR
Product or component type	Phase monitoring relay
Protection type	Sensitivity to phase loss Sensitivity to phase reverse Phase unbalance, 2...15 %
Network type	AC
Network frequency	50...60 Hz
Voltage protection	340...480 V
Tripping threshold	340...480 V AC

Complementary

[Us] rated supply voltage	440 V AC
Mounting support	35 mm DIN rail Panel
Contacts type and composition	1 C/O (PL)
Short-circuit and overId prot	By 4 A gG fuse
[Ue] rated operational voltage	Power circuit: 480 V AC 50...60 Hz IEC 60947-4-1
[Uimp] rated impulse withstand voltage	6 kV IEC 60947-4-1
Reset	Manual reset Electrical < 1 s by interruption of power supply
Display type	2 LEDs
Power consumption per relay	< 2 W
Connections - terminals	Control circuit: 2 lug-clamp 1...2.5 mm ² - flexible - without cable end - M3.5 Control circuit: 2 cable 1...2.5 mm ² - flexible - without cable end - M3.5 Control circuit: 2 cable 1...2.5 mm ² - flexible - with cable end - M3.5
Tightening torque	1.7 N.m for control circuit - lug-clamp, cable - 7 mm head
Height	79.3 mm
Width	50 mm
Depth	106.5 mm
Product weight	0.21 kg

Environment

Standards	IEC 60947-4-1
IP degree of protection	IP20 IEC 60529
Ambient air temperature for operation	-20...60 °C IEC 60947-4-1
Ambient air temperature for storage	-30...80 °C
Operating altitude	2000 m
Fire resistance	650 °C IEC 60695-2-12 960 °C UL 94
Shock resistance	15 gn for 11 ms IEC 60068-2-7
Vibration resistance	4 gn on panel mounting IEC 60068-2-6 2 gn on 35 mm DIN rail IEC 60068-2-6
Dielectric strength	2 kV at 50...60 Hz in between case and circuit IEC 60255-5 1 kV at 50...60 Hz in between contact IEC 60255-5 2 kV at 50...60 Hz in between circuit IEC 60255-5
Surge withstand	6 kV IEC 61000-4-5

Electromagnetic compatibility	Resistance to electrostatic discharge 8 kV air, 6 kV contact IEC 61000-4-2 Resistance to radiated electromagnetic fields 10 V/m level 3 IEC 61000-4-3 Resistance to fast transient 2 kV IEC 61000-4-4 Conducted RF disturbances 10 V EN 61000-4-6 Conducted RF disturbances class A EN 55011
[I _{th}] conventional free air thermal current	5 A, control circuit
Permissible current	250 V, 5 A